

AS5160™ & AS5160T™

Walk-Behind Scrubbers

Simple, rugged and affordable

www.usviper.com



Intuitive control panel with hour meter and battery capacity display.



Available with wet batteries or maintenance-free AGM batteries and onboard charger.



Heavy duty cast aluminum squeegee assembly for efficient water pick-up.

PART OF THE NILFISK GROUP



AS5160™ & AS5160T™

Walk-Behind Scrubbers

Simple

- Intuitive control panel with hour meter and battery capacity display
- Brush and pad driver can be un-installed automatically
- Speed reducing gear drive system of the traction drive version (AS5160T) ensures smooth operation with minimum effort

Rugged

- Robust chassis system and roto-molded tanks, engineered to withstand heavy, daily use
- Heavy duty cast aluminum squeegee assembly for efficient water pick-up
- 5 year warranty; 8 year warranty on roto-mold components

Affordable

- 16 gallon tank and 20 inch cleaning path deliver maximum cleaning productivity
- Available with wet batteries or maintenance-free AGM batteries and onboard charger

Technical Specifications

Description	AS5160™	AS5160T™
Power	850 W	1,090 W
Dimensions (L x W x H)	52 x 22 x 39 in (1,310 x 550 x 1,000 mm)	52 x 22 x 39 in (1,310 x 550 x 1,000 mm)
Vacuum Motor Power	350 W	350 W
Traction Motor Power	-	150 W
Brush Motor Power	450 W	450 W
Voltage	24 V (2 x 12 V)	24 V (2 x 12 V)
Noise Level	69 ± 3 dB A	69 ± 3 dB A
Cleaning Width	20 in (510 mm)	20 in (510 mm)
Maximum Working Efficiency	23,680 ft ² /hr (2,200 m ² /hr)	23,680 ft ² /hr (2,200 m ² /hr)
Solution / Recovery Tanks	16 gal (61 L)	16 gal (61 L)
Solution Flow (Min/Max)	0 - 0.63 gal/min (0 - 2.4 L/min)	0 - 0.63 gal/min (0 - 2.4 L/min)
Squeegee Width	31 in (790 mm)	31 in (790 mm)
Rear Wheels Diameter	3 in (2 pcs)	3 in (2 pcs)
Vacuum Suction	47.2 in (1,200 mm H ₂ O)	47.2 in (1,200 mm H ₂ O)
Brush Speed / Brush Pressure	150 rpm / 60 lb (27 kg)	150 rpm / 51 lb (23 kg)
Battery Options	105 / 130 Ah wet; 105 Ah AGM	105 / 130 Ah wet, 140 Ah AGM
Battery Compartment Dimensions	14 x 14 x 12 in (350 x 350 x 300 mm)	14 x 14 x 12 in (350 x 350 x 300 mm)
Run Time Per Charge	2.5 hours	2.5 hours
Onboard Charger	10 A, 100 V~240 V	10 A, 100 V~240 V
Shipping Weight	254 lb (115 kg)	271 lb (123 kg)
Climbability	2%	2%
Packaging Dimensions	54 x 24 x 48 in (1,370 x 600 x 1,220 mm)	54 x 24 x 48 in (1,370 x 600 x 1,220 mm)

Specifications are subject to change without notice.



9435 Winnetka Avenue North
Brooklyn Park, MN 55445
Phone: 800.989.2235
Fax: 800.989.6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
Phone: 800.668.8400
Fax: 800.263.5111

©2017 Nilfisk, Inc. Form L3456V 12-4-17